

WIRELESS BROADBAND LICENSED NETWORKING SYSTEM FOR LOCAL AND WIDE AREA NETWORKING

5 INVENTORS: Marvin Ward, Chris Vizas and Shant Hovnanian

[0001] CROSS-REFERENCE TO APPLICATIONS

[0002] This application is related to, and claims priority from U.S. Provisional Patent
10 application no. 60/513,419 on October 22, 2003 by Ward et al. titled "Wireless Broadband
Licensed Networking System for Local and Wide Area Networking", the contents of which
are hereby incorporated by reference.

[0003]

TECHNICAL FIELD

15 [0004] The present invention relates to broadband wireless networking systems and
more particularly to dynamically adjustable wireless transmission systems.

BACKGROUND ART

[0005] The available Radio Frequency (RF) spectrum continues to become
20 increasingly crowded, in part due to the rapidly growing demand for wireless solutions to the
"last mile in the loop" distribution problem. Subscribers located in a number of pockets of
coverage, particularly certain urban areas, share modest amounts of bandwidth and
experience limited bandwidth availability. Moreover, power in the frequencies allocated for
point-to-point and point-to-multi-point RF use often has to be reduced to avoid interfering
25 with adjacent frequencies servicing microwave routes and cellular networks.

[0006] There is a need for a point-to-point and point-to multi-point RF systems that
makes better use of the limited available frequencies, and preferably a system that can
operated at power levels that do not interfere with adjacent microwave signal.

30 DISCLOSURE OF INVENTION

[0007] The licensed microwave radio multi-functional broadband system of this
invention overcomes the above identified disadvantages by providing a dynamic central-to-
remote management system and multiple edge smart wireless hubs.

35 Phase Shift Keying (QPSK) and Orthogonal Frequency Division Multiplexing (OFDM)
allowing frequency reuse. In a preferred embodiment, the system also automatically selects
between point-to-point antennas, point-to-multipoint antennas arranged in typically six equal
60° degree sectors, and an omni-directional broadcast antenna. The system of this invention
also includes an intelligent data IP packet measurement system that dynamically determines
40 and controls the network Quality of Service [QoS] through software. The automated control
may include throttling power up and power down to meet changing effects of transmission
parameters in substantially real time.

[0009] In a preferred embodiment, the transmitting antenna system has as many as six
orthogonal sector antennas for radiating RF signals, as well as point-to-point parabolic
45 antennas and an omni-directional broadcast antenna. Furthermore, the system is capable of
automatically receiving and transmitting at least three types of modulated signal types,
namely QAM, QPSK, and OFDM, to optimize transmission based on parameters such as path
distance, bandwidth, and quality of service [QoS] in point-to-point and point-to-multipoint
RF links.

50 [0010] In a preferred embodiment, the system also has one or more remote smart edge
wireless hub capable of receiving and transmitting the preferred signal types, namely QAM,
QPSK, and OFDM modulated signals. The remote smart edge wireless hub antenna system is
also capable of adjusting polarizations orthogonally to achieve minimum crosstalk and
maximum isolation from adjacent frequency interferences, and may also transmit and
55 receives RF signals over different path and carrier frequency to establish two or more RF
paths.

[0011] In a preferred embodiment of the invention, each RF transmitting and
receiving channel is coupled to a payload Internet Protocol (IP) switch. The microcontroller
associated with the pro-band core microwave radio contains the lookup file database and uses
60 it to maintain strict control of the network, the IP payload data, and the smart edge wireless
hubs.

[0012] The system provides for a variety of one-way and two-way communications
services, including connectivity to Wi-Fi access points, private and public Internet access, IP
video streaming, and voice using internet protocol (VoIP) and emergency or public services
65 channels. Dynamic bandwidth control is employed along with very fast payload switch
routing using quality of service (QoS) monitoring and selection circuitry. Using fast packet

switching, the system has the ability to select the error encoding algorithm, RF path route diversity, polarization, frequency diversity and modulation type, to achieve a desired QoS requirement, which it can measure and verify. The systems user roaming channel is always
70 on hot and ready to respond by accepting a user request for broadband service, as a user jumps on and off at will controlled through a pre-registered access user authentication code lookup file that automatically identifies the user upon its first entry when logging onto the system at any point in the network.

[0013] The smart edge hub controller allows pro-band users to request and
75 dynamically change a destination address and bandwidth requirements per user needs in virtually real time from Data Grid Gateways. The Data Grid Gateway setup provides bandwidth and destination information of the requesting subscriber. The user can enter or exit at will. The data packet destination cell carries at all times, an authorization key code that is pre-assigned and opens an available RF channel embedded in assigned radio
80 bandwidth and transmission frequency.

BRIEF DESCRIPTION OF DRAWINGS

[0014] FIG. 1 represents a core-radio transmitting and receiving to smart edge
85 wireless hubs according to the preferred embodiment of the invention making up one data grid.

[0015] FIG. 2 represents an exemplary embodiment of the invention comprising six transmit and six receives RF paths representing transmitted signals sent out and received from six smart edge wireless hub sites through six antenna sectors.

90 [0016] FIG. 3 represents an exemplary embodiment of the invention in which an RF ring architecture is formed from the pro-band core microwave radio RF path and smart edge wireless hubs on one of two available polarizations and RF paths.

[0017] FIG. 4 is a plan view showing two clusters of pro-band core microwave radios internetworking horizontal and vertical polarizations in order to maintain the desired QoS
95 performance.

[0018] FIG. 5 illustrates reuse of four frequencies in six-sectors.

[0019] FIG. 6 represents a data grid gateway with four edge smart wireless hubs demonstrating typical polarization configuration for frequency reuse in one cluster of four smart edge wireless hubs.

100 [0020] FIG. 7 illustrates pro-band core microwave connectivity for setting up roaming channels, emergency public channels routing between edge smart hubs and routing through a matrix over RF paths forming dual channel seamless paths.

[0021] FIG. 8 is a block diagram of one pro-band core microwave radio that using three modulation and encoding methods selected through IP switch based on user
105 requirements.

[0022] FIG. 9 is a block diagram of one pro-band core microwave radio implementing orthogonal frequency division modulation with signal management and flow configured as illustrated in FIG. 8.

[0023] FIG. 10 represents a further embodiment of the present invention.
110

BEST MODE FOR CARRYING OUT THE INVENTION

[0024] During the course of this description like numbers will, as far as possible, be used to identify like elements according to the different figures, which illustrate the invention.

115 [0025] To understand the invention it is easiest to focus on the smallest common element, namely, the single data grid comprising a pro-band core microwave radio and system core-micro-controller and internet protocol (IP) switch and a smart edge wireless hubs, as illustrated in FIG. 1. Together, the pro-band core microwave radio, also known as the core-radio, the core-micro-controller and the IP switch constitute a central processing
120 unit. The connectivity between the data grid elements s through the Orthogonal Frequency Division Multiplexing (OFDM) modem and through the six sector antennas. Although not shown in FIG. 1, the single data grid may comprise a plurality of smart edge wireless hubs. A data grid network is formed from a series of such single data grids.

[0026] FIG. 2 shows a number of smart edge wireless hubs, initially connected
125 together by transmission and reception parameters that depend upon the pre-login records held in file within the local core-micro-controller. There may as many as hundreds of smart edge wireless hubs, connected through vertical and horizontal polarized signals, with QPSK, QAM and/or OFDM modulation of RF channels directed by the pro-band core microwave

and managed by a single core micro controller. This entire embodiment forms one entire data
130 grid network element and for shorter descriptive purposes, is referred herein as a single
cluster site. Smart edge wireless hubs may be positioned physically anywhere within the
cluster if within RF distance operating range. Operating range is considered satisfactorily if
within the cluster site RF operating range with either modulation type applied, desired quality
of service (QoS) standards can be met. The smart edge wireless hub communicates via RF
135 transmission. FIG. 1 illustrates only a single RF channel directed to one smart edge wireless
hub channel. FIG. 2 illustrates a number of smart edge wireless hubs communicating with the
pro-band radio over many RF channels.

[0027] FIG. 3 further illustrates communication between two smart edge wireless
hubs over RF channels.

140 [0028] A block diagram schematic of a preferred embodiment of the transmitters and
receivers is illustrated in FIG. 4. Four transmitters are at the omni directional radiating node
of a group of cells arranged in a geographical array. A digital four channel multiplexer
housed as a part of the pro-band core microwave radio frequency reuse plan, provides up to
four data streams having digital modulation and connected to the antenna array where each
145 radiate RF signals towards multiples of smart edge wireless hubs situated in various positions
within the six sectors of the antenna array path. Each of the antenna arrays are fed OFDM
signals with digital modulated content sent over each one of the antennas that form part of
typically six radiating sectors.

[0029] The signals arrive at the receiving smart edge wireless hub antenna and,
150 depending upon the modulation scheme selected, each signal can be selected remotely by the
pro-band core microwave radio core microcontroller, depending upon the quality of service
(QoS) received in both directions of transmission. Typical performance includes the two
operating modulation schemes depending upon distance between the smart edge wireless hub
and pro-band core microwave radio, is selectable by the core microcontroller.

155 [0030] When a smart edge wireless hub is placed in service a relative short distance
from the pro-band core microwave radio, the signal is typically selected to have QAM or
QPSK modulation so as to provide maximum possible payload transfer (bandwidth). A smart
edge wireless hub located a longer distance from the core-radio would, however, operate
using yet another modulation and encoding type that has an extended range but may have
160 less bandwidth availability such as, but not limited to, OFDM.

Refer to FIG. 6, the transmitting antenna array provides a four cluster polarization arrangement for radiating RF signals with digital coded data sent out upon initial turn-up for testing the RF path under program control of the core microcontroller in the pro-band core microwave radio. This polarization arrangement allows the reuse of frequencies in adjacent channels within the same cluster. The received RF coded signal is analyzed in one direction only; transmission of RF signal from the pro-band core microwave radio, using all four RF signal types are tested and logged in memory for future QoS comparison and reference. Specific operating parameters can impinge on the RF signal; degraded weather can change an RF signal quality and reference causing even another modulation format to be selected. Path analysis is performed during initial turn-up and through automatic selection of different reduced power; settings with modulation types and polarization choices can take place in milliseconds without loss of signal. Transmitted RF signals received from more than one source may undergo RF signal variances in quality due to weather or varying distances from the pro-band core microwave radio. However, any intrinsic differentiation between each frequency is usually quite wide and unintentional reception will typically not take place. The pro-band core microcontroller illustrated in FIG. 3 controls the frequencies and power settings for the path between site C and site D even though these are remote links isolated by RF path from the pro-band core microwave controller. In a preferred embodiment, the transmission frequency is selected by reference to a centralized or distributed registrar of all frequencies available to all of the smart edge hubs.

[0031] RF signals arriving at site D receiver enter into the smart edge wireless hub reaching a receiver detector where composite signal detection takes place and IP payload content is decoded in the form of IP packet data. After extraction, these packets are aligned according to IP address code carried in the header located within the data formatted packet. Data directed over routes linking sites C, D back to the pro-band core microwave radio are switched automatically, dependent on actual load on each radio path and available bandwidth availability. The incoming signal and resultant retrieved packets all arrive within milliseconds of each other and delay is considered negligible. The QPSK / QAM transmit RF frequencies transmitted to a smart edge wireless hub are never greater than two, one applied to horizontal and a second to vertical polarizations. During the initial RF path setup and testing sequence, the controller will exercise tests of all frequencies and transmission types and log the results in database.

[0032] Now turning to FIG. 1 and FIG. 9, the pro-band core radio and omni antenna provides a second optional RF path to properly equipped smart edge wireless hubs positioned remotely to any one of up to six antenna sectors providing coverage to wide area locations and each antenna sector covers a physical space area, typically 60⁰ degrees per antenna and six antennas, as illustrated in FIG. 3, which would cover 360⁰ degree radius, sending RF signal outward, to a range of about one to eight miles, depending upon transmit power settings, type of system transmit signal encoding format applied, physical terrain makeup and variable weather conditions within an area. Referring to FIG. 7, the second RF path transmitted that links each site provides additional bandwidth expansion setting up an alternate channel for special subscriber services that may include, but are not limited to, a hot on channel for subscriber easy access to roaming, emergency community communications and dynamic bandwidth expansion of the primary channel bandwidth beyond the normal payload sized network provided in similar systems. A hot on channel allows real-time access.

[0033] A primary RF channel transports normal payload IP data traffic while operating on horizontal polarization with separate assigned frequencies, and while the secondary RF channel operates on vertical polarization being assigned a different frequency; both channels are controlled through the micro controller and payload IP switch located at the pro-band core microwave radiolocation. This extended bandwidth is separated into individual payload nodes, providing part time and full time access for services. The pro-band core microwave radio operating with virtually any number of smart edge wireless hubs provides several unique and separate expansions and use of microwave radio bandwidth to accommodate subscribers as listed in the following table:

| Primary RF Path | | | |
|----------------------|-----------|---------|---------|
| Subscriber Use | Channel | Path # | Payload |
| IP Traffic | Channel A | Path #1 | IP Data |
| Secondary RF Path | | | |
| Subscriber Use | Channel | Path # | Payload |
| IP Traffic | Channel A | Path #1 | IP Data |
| Roaming Hot On | Channel B | Path #2 | IP Data |
| Emergency Community | Channel B | Path #2 | IP Data |
| Dynamic Load Control | Channel B | Path #2 | IP Data |

[0034] Illustrated in FIG. 7, the above primary and secondary RF channels provide an advantaged method of expanding the systems bandwidth without adding expensive external peripheral equipment for bandwidth control and multiplexing. This aspect of the invention provides an extended bandwidth and service offering to the network user who simply and quickly jumps on and off the smart edge wireless hub at any given site and any time. This will greatly simplify the typical PC user's efforts to link up and tear down a network connection. In FIG. 4, the subscriber user can disconnect or disengage from the data grid area site D and smart edge wireless hub and travel to a second and different data grid site A, and simply and quickly connect at this different smart edge wireless hub site and start communicating as if the device never left the first site D network. This seamless transfer can take place only through shared central data bank storage of subscriber information whereby data can be flagged for hold status as the subscriber disengages at the first location and readdressed the information at the original site placed in hold status and later reappeared at a different data grid network. The smart edge wireless hub software program sends bursting data up-stream to share status information with other microcontrollers and payload IP switch on a continuous basis during all subscriber sessions, including sign-on, sign-off, stop sending and hold/transfer status. The actual software code and data instructions are defined under separate patent references.

[0035] Now turning to bandwidth expansion using a secondary channel, this function is achieved with the present invention more economically and essentially with the same antenna systems that support a second RF channel very easily and with limited new expense. Now again turning to FIG. 4 specifically to smart edge wireless hub designated sites B, D are both linked back to the pro-band core microwave radio site 001A. Sites B and D are equipped with a second transmitter/receiver system numbering the total of two antennas that sets up a second antenna path between Site D and Site B in such configuration as to form a triangle RF transmission path between the three sites identified. Each sectional single path of the three paths forming this RF ring operates dual RF paths having vertical and horizontal polarizations applied. Each RF path carries IP packet payloads in the form of primary A RF channel and secondary B channel with B channel content illustrated in FIG. 7, carrying roaming hot on line traffic, emergency community traffic, the dynamic load control channel. In addition, this RF triangle arrangement provides security surveillance and IP data for real

time video cameras, security door locks and a highly secured path for activated security coded keys. The triangle RF system transports cipher protected packets of highly classified data and each of these cipher protected packets scrambled in session to form a dual path of data where a data word is sliced and assigned into digital coded words in IP formats and again separated into two data RF path flows, one transmitted on path B and path D to reach site B and the second transmitted from the pro-band core microwave radio is directed to site D by path B. Note that two path hops are required in one leg while only one RF path or hop is required to complete the path from pro-band core microwave radiolocation to site D. The invention of this routing provides digital data transported over paths B to D will arrive at site B ahead by a few milliseconds of data that passes through site D and repeated on to site B requiring two RF hops. The data first arriving at site B carries an assembly and de-assembly code for assembling and taking apart data bits arriving on the delayed channel. The transmitted key is therefore sent the shortest route and a different route than the data packet carrying the actual payload. The supervisory code is never transmitted over the same path with data content that it controls.

[0036] Cipher-lopes are electronic secured packets of data that are highly secured through packet-coded keys, assembled in highly secured sealed electronic digital packets of IP data that are coded close, and sent over the above link to highly secure the data content. Should the packed ever be opened during transit, a flip-flop logic circuit will leave a sign of the intrusion and breach of security. The RF path is constructed in physical form to provide full path and system diversity through two RF links. The two data paths reach their secured environment only in an proper protected environment where the two keys match a series of ever changing digital coded word in the form of management instructions and only after being fully exercised and tested with these digital words are these words allowed to be used to de-cipher and assemble the packets of data at the receiving station, demanding duly authorized code to open and detect the content.

[0037] Turning once again to FIG. 7, the architecture of a single cluster illustrated in FIG. 2 defines the method used to establish a primary channel and secondary channel covered above. The cluster illustrated and referenced as FIG. 7 has four edge smart wireless hubs shown as circles around a center cell representing the pro-band core microwave radio, the microcontroller, and payload switch. One cluster when attached by RF to other clusters provides internetworking connectivity and control to multiples of edge smart wireless hubs

280 illustrated in FIG. 4. Referencing FIG. 7 and drawing attention to the connecting outside
illustrated lines encircling all four edge smart wireless hubs, these represent the primary
channel, and a second inside line paralleling the outside lines is the secondary channel. Note
that in FIG. 7 and FIG. 4, all four edge smart wireless hubs are interconnected and
communicate to each other by means of establishing the RF path between each multiples of
285 edge smart wireless hub back to the pro-band core microwave radio sites 001A and 002A,
each at the center of a cluster. Note that the multiple RF paths are optional for establishing
and maintaining a well-secured and seamless infrastructure that is able to support the highest
of transmission protection for securing cipher-lopes.

[0038] Links from the pro-band core microwave radio-connecting cluster of FIG. 3,
290 and FIG. 7 to other outside clusters are illustrated by the two lines connecting by way of radio
path having both horizontal and vertical polarizations. These RF paths are direct point-to-
point RF channels on both vertical and horizontal polarizations.

[0039] Drawing configurations FIG. 3 and FIG. 7 illustrate the invention and system
path configuration that supports transmission of cipher-lope in the form of secured data
295 between multiples of edge smart wireless hubs located in and outside the cluster that is
uniquely capable of forming a microwave ring for RF transmission protection in the event
that one path is lost due to transmission failure. As a general rule, content and setup /
takedown instructions are never sent in the same IP packet and never over the same RF paths.
Routing of the Cipher-lope packets is controlled by pro-band core IP switches and micro
300 controller. In routes where the Cipher-lope destination may take it across seamless
boundaries from one cluster site to another cluster site as illustrated in FIG. 4., then setup
and take down procedures are passed from the originating cluster to the second cluster pro-
band core micro controller.

[0040] This security level can be utilized for IP security of any sort, outside Cipher-
305 lopes applications. Voice over IP (VoIP) and video digitized content can be provided a
higher level of security on the licensed radio band. FIG. 8 and FIG. 9 diagrams show
different modulation types used, namely OFDM, QAM and QPSK. All three-modulation
types have some advantages and trade-offs. As discussed earlier and referenced in FIG. 6,
setting polarizations and throttling transmit power down to an accepted QoS level enhances
310 the overall performance of the network.

[0041] Now turning to FIG. 9, the RF microwave transmission system adapts orthogonal frequency division modulation at all edge smart wireless hubs broadcasting RF to achieve frequency reuse efficiency and to provide improved RF reception performance and local loop reliability. OFDM signals are transmitted in a pattern of up to 360^0 degrees geographical coverage at A, B, C D, and E sites illustrated in FIG. 3 and 4. Coexistence with other point-to-point RF links is accomplished by using cross-polarization, separating adjacent channel interferences by proper frequency selection, the use of highly directional antennas with high cross-polarization rejection, giving consideration to physical placements of antennas, and using antennas with low side lobes, as well as applying error-correction. To reduce co-channel interference, the system measures transmitted power of each leg by taking measurement samples of each RF receiver level sensitivity and bursting each of these results in the form of packet overhead back to the transmitter end allowing the microcontroller to take action and throttle the transmit power to a level that results in reliable and useable transmission signal quality and is further automatically measured against system preset QoS reference levels.

[0042] Frequency reuse is employed in each edge smart wireless hub to expand the capacity of each pro-band core microwave cluster. FIG. 5 illustrates a typical four frequency six sector frequency re-use pattern applied to each six sectors and antenna array that cover an geographical area up to 360^0 degrees diameter further illustrated in FIG. 1.

[0043] Turning to FIG. 4 within a cluster, polarization of each sites A, B, C, and D are setup as defined to minimize adjacent transmit frequency interference. The full frequency band is reused for maximum frequency spectrum coverage in each smart edge wireless hub site. The microcontroller detects any RF link loss and will reverse direction so that information flow in these protected links is un-interrupted. The edge smart wireless hubs A, B, C, and D form an outside transmission ring, as well as communicate with the center pro-band core microwave radio, as illustrated in FIG. 4. The pro-band core microwave radio is able to transmit over four paths, namely the A1 path to B1 path and C1 path to D1 path, out to each respective outlying edge smart Wireless Hub, A Hub, B Hub, C Hub and D Hub.

[0044] Now turning to FIG. 8 and FIG. 9, the user interface is representative at 20 input to a 10/100 base T copper or SX fiber interface to the transmit input. Note that at 20 the received signal is output to the end user on a LAN and the input from LAN is the transmitted payload.

[0045] The IP 28 Ethernet signal passes through the transmit interface to a stage called IP data switch 5, where the packet address headers are detected and read and the IP packet signal routed thru. The common channel is aligned throughout each and every site, thus originating a seamless hot roaming channel, as well as an emergency community channel and dynamic load control channel that operates in each and every outlying smart edge wireless hub. Security of these channels is set up according to the cipher-lope standard of operation, rendering all site bandwidth to be highly secured for both the primary and secondary channels.

[0046] As illustrated in FIG. 1, six signals are received by an orthogonal antenna 15 at the smart edge wireless hub 18 and are interfaced 16, 17 into the smart edge wireless hub 18 controlled by the remote micro controller 19 at the remote site. FIG. 1 illustrates the QPSK and QAM transmission path 14 between the antenna 15 at the smart edge wireless hub and the antenna 2 at the pro-band core microwave radio receiver input and transmits 1.

[0047] The embodiments of the invention described above provide a licensed microwave radio multi-functional broadband system that includes dynamic central to remote management system having multiple numbers of installed edge smart wireless hubs. The system is capable of selective transmission type QAM, QPSK and orthogonal frequency division multiplexing system for broadcast over point-to-point, point to multipoint and omnidirectional antenna arranged in six equal 60° degree arrays.

[0048] There is also an intelligent data IP packet measurement system through software dynamically reads and controls Quality of Service [QoS] and throttles power up and power down to meet changing effects of transmission parameters in virtual real time.

[0049] The system has receiving remote antennas capable of changing polarization settings to allow frequency reuse, and with programmable receive low noise block (LNB) filters to minimize adjacent RF signal cross talk.

[0050] The system's antenna system has a six sector antenna stage, and an antenna that applies QAM and QPSK modulation selection automatically, depending to achieve the desired path distance, bandwidth, and quality of service [QoS].

[0051] In one embodiment of the system, the antenna array combines flat panel and parabolic antennas together to serve QAM, QPSK and OFDM RF transmission.

[0052] In another embodiment of the system the transmitting antenna system includes a remote smart edge wireless hub capable of receiving and transmitting three formats, QAM, 375 QPSK and OFDM signals in the same mechanical antenna.

[0053] In one embodiment of the system, a remote smart edge wireless hub antenna system adjusts polarizations orthogonally to achieve minimum crosstalk and maximum isolation to lower adjacent frequency interferences.

[0054] In one embodiment of the system a remote smart edge wireless hub antenna 380 system that transmits and receives RF signals of different path alignment and carrier frequency types to establish two independent RF paths.

[0055] In one embodiment of the transmitting and receiving system there is a primary RF channel A linking local and remote smart end wireless hubs for IP data traffic, and a secondary RF channel B linking for user roaming hot-on. There may also be a secondary RF 385 channel B for emergency community channel service and for dynamic load control.

[0056] In one embodiment of the invention, there is also a dynamic RF re-routing in ring configuration system that includes a network RF path direction that can be redirected upon failure of the primary RF path or secondary RF path on a seamless basis.

[0057] In one embodiment of the invention there is a network RF path sending data 390 over an RF network with data content divided into two or more paths to support cipher-lope highly secured content by sending setup/takedown code in direct path and content in second and longer path.

[0058] One embodiment of the invention includes a physical encapsulated packet that contains a header referenced to activate an onboard physical circuit flip/flop control to 395 indicate packet-tampering status.

[0059] A further embodiment of the invention includes a secured encapsulated packet management system that reads status at a physical point along the transmission path in virtual real time, and with electrical / physical circuit status.

[0060] In another embodiment of the system the pro-band core microwave, 400 microcontroller, and IP switch includes a user time-share of bandwidth on a part time basis on 7 x 24 x 365 time having access at any smart edge wireless hub location. There is also provision for a user, or multiple users, to have time-share access to emergency channel use in case of local emergency or local and national disasters.

[0061] In a further embodiment of the system the pro-band core microcontroller and
405 IP switch includes a bursting data stream up-link and down link from the smart edge wireless
hub to and from the pro-band core microcontroller and IP switch to measure QoS and make
system equipment adjustments to outlying equipment power, polarization, switching
modulation types for management of pro-band core network.

[0062] There may also be a system setup for establishing a data grid around the pro-
410 band core microwave and multiples smart edge wireless hubs that provide exclusive and non-
exclusive security services in the form of security surveillance cameras, door/window alarms
or other entrance locks and including proximity alarms, remote alarms, temperature controls,
fire and water alarms that report to distributed or centrally located points.

[0063] In one embodiment the pro-band core microcontroller and IP switch and smart
415 edge wireless hub controller includes an enhanced forward error correction coded algorithm
signal monitors IP data performance for errors, dropped packets, noise on transport facilities,
as well as capability for the system processors to transfer payload onto a pre-selected
alternate route.

[0064] There may also be a load balancing control capable of determining when
420 routing IP packets from primary channel are at or near maximum load, and then ensuring that
packets are routed over secondary channel for dynamic load control and to add bandwidth.

[0065] In a further embodiment of the system the pro-band core microcontroller and
IP switch and smart edge wireless hub controller includes a roaming secondary channel
dedicated to permanently un-numbered smart edge wireless hubs covering an entire
425 metropolitan area network.

[0066] There may also be a secondary channel dedicated to permanently open
connectivity for emergency use throughout a metropolitan area network providing a private
channel for communicating and sending data in emergency conditions.

[0067] In one embodiment of the system two smart edge wireless hubs may operate
430 as a master smart edge wireless hub configured as master controller and a slaved smart edge
wireless hub configured as slaved to extend IP service between two locations.

[0068] There may also be a master smart edge wireless hub-A location configured as
master controller and a slaved smart edge wireless hub-B location, each configured with two
antennas that communicate between each smart edge wireless hub A to B and to pro-band
435 core microwave radio, micro controller, and payload switch.

[0069] The pro-band core system delivers a variety of one and two-way communication signals carrying multi services of private and public Wi-Fi networks, and digital two-way transmission with internet content, IP video, data and voice [VoIP] packets using IP internet protocol

440 [0070] While the invention has been described with reference to the preferred embodiment thereof, it will be appreciated by those of ordinary skill in the art that various modifications and changes can be made to the structure and functions of the individual parts of the system without departing from the spirit and scope of the invention as a whole.

445

INDUSTRIAL APPLICABILITY

[0071] The present invention has industrial applicability to the telecommunications industry. In addition, the present invention is suited to use in the industries of communications service provision, including cellular and data communications. The present invention is also suited for use in the emergency service industry.

450